


Advanced Grid Jobs I – Collections & Parametric Jobs



Outline

- ❑ Large number of jobs – WMS overhead ?



- ❑ Job Collections
 - Different applications as a single request
 - ✓ Command line option ‘--collection’
 - ✓ Advanced Collections
- ❑ Parametric Jobs
 - Same code with different parameters

Job collections

❑ Set of independent jobs submitted all together

- Submit
- Monitor
- Control

... as a single request



❑ Sharing Sandboxes

- Sub-jobs with common input files
- 1 copy of each file is transferred

Simple Collections

- `glite-wms-job-submit -d $USER -o joblds --collection <jdl_dir>`
 - `<jdl_dir>` files:
 - ✓ `hostname.jdl`
 - ✓ `echo.jdl`


hostname.jdl:

```
Type = "Job";
JobType = "Normal";
Executable = "/bin/hostname";
Arguments = "-f";
StdOutput = "simple.out";
StdError = "simple.err";
OutputSandbox = {"simple.out","simple.err"};
ShallowRetryCount = 3;
```

echo.jdl:

```
Type = "Job";
JobType = "Normal";
Executable = "/bin/echo";
Arguments = "Hello Grid!";
StdOutput = "simple.out";
StdError = "simple.err";
OutputSandbox = {"simple.out","simple.err"};
ShallowRetryCount = 3;
```

Advanced Collections submit



Advanced Collections Output

```
mooc@ui:~/moo...ples/7_collections
mooc$ cd moocexamples/7_collections/
mooc$ ls
collection.jdl  script_node1.sh  script_node2.sh
mooc$ vim script_node1.sh
mooc$ vim script_node2.sh
mooc$ nano collection.jdl
mooc$ nano input_common1.txt
mooc$ nano input_common2.txt
mooc$ ls
collection.jdl  input_common1.txt  input_common2.txt  script_node1.sh  script_node2.sh
mooc$ startGridSession tutor
mooc$ glite-wms-job-submit -d $USER -o /home/mooc/moocexamples/jobIDs collection.jdl
```

Job Detail

https://wms2.grid.sara.nl:9000/zwfvzAwwS9Szwrw9FAtsPA

Job ID	https://wms2.grid.sara.nl:9000/zwfvzAwwS9Szwrw9FAtsPA
CREAM ID	
Parent job	
Status	Done
Type	Collection
Seed	WMPROXY
No. of Children	3
Subjob Failed	
VM Status	

Parametric jobs

□ Parameter sweep...

```
#!/bin/bash
for i in {1.. 100}
do
    # Create JDL file and inputs for i'th step:
    [ Some shell scripting here ]
    # Submit the i'th job:
    glite-wms-job-submit -a -o jobIDs param$i.jdl
done
```

□ Parametric jobs:

- Set of jobs to be generated from one JDL
- Same code on different parameters
- JobType = "Parametric";
- Key word: `_PARAM_`
- >[50 – 100] jobs → Choose a pilot job framework

Parametric submit

